

UTILITY PATENT
APPLICATION TRANSMITTAL

(Only for new nonprovisional applications
under 37 CFR 1.53(b))

Attorney Docket No.

000760

Total Pages

First Named Inventor or Application Identifier

Ko KAMBAYASHI and Takashi HIRASAWA

Express Mail Label No.

Check Box, if applicable [] Duplicate

APPLICATION ELEMENTS FOR:
IMAGE PICKUP DEVICE ATTACHABLE TO
ELECTRONIC APPARATUS

ADDRESS TO: Director of Patents and Trademarks
BOX PATENT APPLICATIONS
Washington, D.C. 20231

1. ☒ Fee Transmittal Form (Incorporated within this form)
(Submit an original and a duplicate for fee processing)

2. ☒ Specification Total Pages [17]

3. ☒ Drawing(s) (35 USC 113) Total Sheets [16]

4. ☒ Oath or Declaration Total Pages [5]

a. ☒ Newly executed (original)

b. ☐ Copy from prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed).

i. ☐ Deletion of Inventor(s)
Signed statement attached deleting inventor(s) named in prior application,
see 37 CFR 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation by reference (useable if box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under
Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)

7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)

- a. ☐ Computer Readable Copy
b. ☐ Paper Copy (identical to computer copy)
c. ☐ Statement Verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet and document(s))

9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [XX] Power of Attorney

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications
under 37 CFR 1.53(b))

Attorney Docket No. **000760**

First Named Inventor or Application Identifier

Ko KAMBAYASHI and Takashi HIRASAWA

PAGE 2 OF 3

10. ☐ English translation Document (if applicable)
11. ☐ Information Disclosure Statement ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application
Status still proper and desired.
15. ☒ Claim for Convention Priority ☒ Certified copy(ies) of Priority Document(s)
- a. Priority of _____ application no. _____ filed on _____ is claimed under 35 USC 119.
The certified copies/copy have/has been filed in prior application Serial No. _____.
(For Continuing Applications, if applicable)
16. ☐ Other _____
17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:
☐ Continuation ☐ Division ☐ Continuation-in-part (CIP) of prior application no. ____/____

FEE TRANSMITTAL	Number Filed	Number Extra	Rate	Basic Fee
The filing fee is calculated below				\$690.00
Total Claims	12 - 20		x \$18.00	
Independent Claims	2 - 3		x \$78.00	
Multiple Dependent Claims			\$260.00	
			Basic Filing Fee	690.00
Reduction by 1/2 for small entity				
Fee for recording enclosed Assignment			\$40.00	40.00
TOTAL				\$730.00

UTILITY PATENT
APPLICATION TRANSMITTAL

(Only for new nonprovisional applications
under 37 CFR 1.53(b))

Attorney Docket No.

000760

First Named Inventor or Application Identifier

Ko KAMBAYASHI and Takashi HIRASAWA

PAGE 3 OF 3

[XX] A check in the amount of \$730.00 is enclosed to cover the filing fee of \$690.00 and the assignment recordation fee of \$40.00.

[] Please charge our Deposit Account No. **01-2340** in the total amount of _____ to cover the filing fee and the _____ assignment recordation fee. A duplicate of this sheet is attached.

[XX] The Commissioner is hereby authorized to charge payment for any additional filing fees required under 37 CFR 1.16 or credit any overpayment to Deposit Account No. **01-2340**. A duplicate of this sheet is attached.

18. CORRESPONDENCE ADDRESS

ARMSTRONG, WESTERMAN, HATTORI
McLELAND & NAUGHTON
1725 K Street, N.W. Suite 1000
Washington, D.C. 20006
Telephone: (202) 659-2930
Facsimile: (202) 887-0357

SUBMITTED BY

Typed or Printed Name Ronald F. Naughton

Reg. No. 24,616

Signature

Ronald F. Naughton

Date: June 16, 2000

REN/yap

IMAGE PICKUP DEVICE ATTACHABLE TO ELECTRONIC APPARATUS

BACKGROUND OF THE INVENTION

5 The present invention relates generally to peripheral equipment for use with a notebook personal computer ("notebook PC") or portable terminal, a portable electronic apparatus, a personal digital assistant ("PDA"), and other electronic apparatuses, and more particularly to an image pickup device connectible with the electronic apparatus or hardware. The "peripheral equipment", as used herein, is
10 such hardware as is connectible with a PC body and realizes necessary functions.

 The recent development and spread of notebook PCs, portable terminals and portable electronic apparatuses have increasingly demanded compact and lightweight notebook PCs for portability purposes which nevertheless exhibit such affluent functions on a desk in an office as desktop personal computers ("desktop PCs"). As
15 part of an attempt to achieve such multi-functionality, a device for adding an image pickup function to the notebook PC has been proposed.

 Japanese Laid-Open Patent Application No. 9-128091 discloses a notebook computer that has an image pickup device connectible to a PC card with a cable. However, an image pickup portion including an image-pickup lens is still too large for
20 portability. Japanese Laid-Open Patent Application No. 10-271376 has proposed a CCD camera built-in notebook PC that has improved the portability by mounting the entire CCD camera onto the PC card. Japanese Patent Applications Laid-Open Nos. 8-9215 (or U.S. Patent No. 5,867,218) and 7-322117 (or European Patent Application, Publication No. 683,596) also disclose techniques of building a CCD camera in a
25 card-shaped housing.

 Japanese Utility-Model Registration No. 3011657 discloses an electronic

camera that may be detachably stored in a concave portion provided on a desktop PC body and connected via a connector with the PC body in the concave portion.

A technique of mounting a CCD camera in a hinge portion connecting a liquid display bezel frame and base section of the notebook PC is known in the art as seen in products such as Toshiba's Libretto ff 1100, Panasonic's Let's note/C33EA, Sony's VAIO PCCGC1s.

Attachment techniques of a CCD camera or other USB-compatible units through a USB port instead of a PC card are known in the art as well. For example, Japanese Laid-Open Patent Application No. 11-53060 discloses a notebook PC equipped with a CCD-camera USB port at a top of its display section so that the camera is connectible directly or via cable to the USB port. The USB port is compatible with a printer or keyboard in addition to the CCD camera. As recently as June 21, 1999, Victor Company of Japan, Limited announced a release of a CCD camera (USB capture camera 'MP-UC1') that can be mounted on a notebook PC (mobile PC 'InterLink' MP-C101).

The present inventors have focused attention on a USB-compatible image pickup device having several advantages including plug-and-play and hot plug capabilities. The CCD camera as seen in Victor's MP-UC1 may be likely to be broken by concentrated load of its own weight on a connector portion with the notebook PC when the notebook PC with the CCD camera is lifted. In this respect, conventional configurations for the CCD camera are not sufficient so as to prevent the connector portion such as a USB port from breaking while ensuring its connectivity with universal notebook PCs.

BRIEF SUMMARY OF THE INVENTION

Therefore, it is an exemplified general object of the present invention to provide a novel and useful image pickup device attachable to an electronic apparatus in which the above disadvantages are eliminated.

Another exemplified and more specific object of the present invention is to provide an image pickup device attachable to an electronic apparatus that can prevent the connector portion from breaking while ensuring its connectivity with universal notebook PCs.

In order to achieve the above objects, an image pickup device as one exemplified embodiment of the present invention comprises a connector which is connectible, *e.g.*, electrically or optically, to an electronic apparatus, and a reinforcing portion which is located near the connector and reinforces the connector when the electronic apparatus and the connector connect with each other. The reinforcing portion in this image pickup device may reduce a load that would otherwise apply to the connector, and prevent connector's deterioration in the course of time.

The image pickup device may further comprise an anchor portion and a movable portion. The movable portion includes an image pickup portion, and the connector and the reinforcing portion may be placed on the anchor portion. The reinforcing portion can be stored in the anchor portion so that it can project from the anchor portion. Accordingly, the reinforcing portion may be stored in the anchor portion while the image pickup device is not attached to the electronic apparatus. The image pickup device may further comprise a stand that is connected with the anchor portion and serves to adjust a height of the anchor portion. Consequently, the height of the image pickup device can be varied according to a height of the electronic apparatus to which the image pickup device is attached, reducing a load applied that

would otherwise apply to the connector when the electronic apparatus having the image pickup device is placed on its footprint. The stand may adjust an inclined angle of the anchor portion. Therefore, for example, even if the electronic apparatus is a notebook PC of which a keyboard tilts for ergonomic purposes, a position and orientation of the anchor portion of the image pickup device can be adjusted accordingly, whereby the load to the connector would be eliminated as well. The anchor portion may include a storage portion that can store the image pickup portion. This allows the image pickup device to protect the image pickup portion when unused.

The image pickup device as another exemplified embodiment of the present invention comprises a connector that is connectible, *e.g.*, electrically or optically, to an electronic apparatus, and an attachment portion that enables the image pickup device to be attached to an external apparatus. This image pickup device may be attached to an external device (including electronic apparatus) through the attachment portion. Thus, the image pickup device attached to a desired position may capture a desired subject, and to remove or reduce an area for placement of the image pickup device. The image pickup device may include an anchor portion and a movable portion. The movable portion includes an image pickup portion, and the connector may be placed on the anchor portion. The attachment portion enables the anchor portion to be attached to the external apparatus. The attachment portion may be provided onto the anchor portion so that it can project from the anchor portion. Accordingly, the attachment portion may be attached to any position, for instance, the electronic apparatus may include a display portion, and the image pickup device may be attached onto the display portion through the attachment portion.

Other objects and further features of the present invention will become readily apparent from the following description of the preferred embodiments with reference to accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic perspective view of one exemplified aspect of an inventive image pickup device connected to an electronic apparatus.

5 FIG. 2 is a front view of a CCD camera in which a movable portion is raised (opened) from an anchor portion when a USB connector and a reinforcing portion are stored in the anchor portion.

FIG. 3 is a right side view of a CCD camera in which the movable portion is raised (opened) from the anchor portion when the USB connector and reinforcing
10 portion are stored in the anchor portion.

FIG. 4 is a left side view of a CCD camera in which the movable portion is raised (opened) from the anchor portion when the USB connector and reinforcing portion are stored in the anchor portion.

FIG. 5 is a top view of a CCD camera in which the movable portion is raised
15 (opened) from the anchor portion when the USB connector and reinforcing portion are stored in the anchor portion.

FIG. 6 is a front view of a CCD camera in which the movable portion is raised from the anchor portion when the USB connector and reinforcing portion project from the anchor portion.

20 FIG. 7 is a right side view of a CCD camera in which the movable portion is raised from the anchor portion when the USB connector and reinforcing portion project from the anchor portion.

FIG. 8 is a left side view of a CCD camera in which the movable portion is raised from the anchor portion when the USB connector and reinforcing portion
25 project from the anchor portion.

FIG. 9 is a top view of a CCD camera in which the movable portion is raised

from its anchor portion when the USB connector and reinforcing portion project from the anchor portion.

FIG. 10 is a rear view of a CCD camera in which the movable portion is raised from the anchor portion when USB connector and reinforcing portion project from the anchor portion.

FIG. 11 is a front view of a CCD camera in which the movable portion is folded (closed) into its anchor portion.

FIG. 12 is a right side view of a CCD camera in which the movable portion is folded (closed) into its anchor portion.

FIG. 13 is a sectional view of a CCD camera in which the USB connector and reinforcing portion project.

FIG. 14 is a sectional view of a CCD camera in which the USB connector and reinforcing portion are stored.

FIG. 15 is a rear view of a notebook PC to which a CCD camera is attached.

FIG. 16 is a right side view of a CCD camera for explaining a stand for the CCD camera.

FIG. 17 is a right side view of a CCD camera in which the movable portion tilted by approximately 180 degrees relative to the anchor portion when the attachment portion projects from its anchor portion.

FIG. 18 is a right side view of the CCD camera shown in FIG. 17 attached to an LCD bezel frame of a notebook PC.

DETAILED DESCRIPTION OF THE INVENTION

A description will now be given of an inventive image pickup device 100 connected to an electronic apparatus 100 with reference to FIG. 1. The same

members are designated by the same reference numerals, and a duplicate description thereof will be omitted.

Referring to FIG. 1, an electronic apparatus 100 and the image pickup device 200 are exemplarily shown as, but not limited to, a notebook PC 100 and a CCD camera 200, respectively. The electronic apparatus 100 includes PDAs, handheld PCs, palm-size PCs, wearable computers, portable electronic apparatuses, and portable terminals. The image pickup device 200 includes, but not limited to, digital still cameras, digital movie cameras, disc cameras, digital video cameras, retina recognition devices, fingerprint recognition devices, and the like. The notebook PC 100 may cover A4, B5, sub-notebook, mini-notebook and other sizes. Hereupon, FIG. 1 is a schematic perspective view of the CCD camera 200 mounted on the notebook PC 100 while it is being used. The CCD camera 200 includes an anchor portion 210, a movable portion 220, a focus lens (image pickup portion) 230, a shutter 240, a USB connector 250, a reinforcing portion 260, and a stand 270. A further description will be given of its detailed structure with reference to magnified diagrams shown in FIGs. 2 and 3.

The notebook PC 100 includes a liquid crystal display (LCD) bezel frame 10 and a base 20 that are connected to each other via a hinge 30, and an LCD screen 12 is placed on the LCD bezel frame 10. Typically, the base 20 has a thickness of about 50 mm or less, or preferably about 20 to 30 mm. The LCD bezel frame 10 has a substantially rectangular shape so as to hold the LCD screen 12. As described above, a universal notebook PC may be used for the notebook PC 100 of the present embodiment. However, the image pickup device 200 of the present invention is also applicable, for example, to a notebook PC of a special specification that is equipped with a USB port at the top of the LCD bezel frame 10.

The base 20 includes a keyboard section 40 for typing information in, and the

keyboard may use any type and arrangement. Usable types of the keyboard may include 101, 106, 109 and ergonomics, and usable key arrangements include QWERTY, DVORAK, JIS, new-JIS, and NICOLA (Nihongo Nyuryoku Conthotium Layout).

The base 20 includes an external frame 22 and an aperture 24 provided on the external frame 22, as will be described later with reference to FIG. 15. The base 20 also includes a pointing device 50 that emulates part of mouse functions. Despite the structure shown in FIG. 1, the pointing device 50 may include a mouse, a trackball, a trackpad, a tablet, a digitizer, a joystick, a joypad, a touch panel, and a stylus pen.

The base 20 is provided with a connecting portion (USB interface, not shown) connectible with the USB connector 250, and this interface and USB connector 250 serve to establish an electric connection between the CCD camera 200 and the notebook PC 100. Through this connecting portion, data is transmitted from the CCD camera 200 to the notebook PC 100. Similarly, control information is transmitted from the notebook PC 100 body to the CCD camera 200.

USB (Universal Serial Bus) is a serial interface for PC peripherals, serves to bring connecting cables together, and supports a plug and play or hot plug. It permits a multiplex connection up to 128 ports, and supports two kinds of transfer rates, 1.5 Mbps for a low-speed mode, and 12 Mbps for a high-speed mode. Four varieties of transfer modes (bulk, control, interrupt, and isochronous modes) are available. The isochronous mode is used for preferentially transferring at intervals data required for a real-time transfer such as a movie and sound. Its signal lines consist of four wires (two communication lines and two power lines). As described above, the USB is suitable for a low- or mid-speed communication interface (ranging from 1.5 Mbps to 12 Mbps), and thus preferably applied to capturing a movie of midrange quality in resolution and display speed (e.g., 320 x 240 pixels, and 5 or 6 frames/sec.), therefore serving as an inexpensive and standardized communication interface.

09594513.061600

However, the connector of the image pickup device 200 of the present invention is not necessarily limited to the USB connector 250, and applicable interfaces exemplarily include, but are not limited to, a parallel interface (e.g., IEEE1284 and IEEE1394), a serial interface (e.g., RS-232C and RS-422), IDE (including Enhanced IDE and the like), SCSI (including SCSI-2, SCSI-3), Ultra ATA, ATAPI, 10BASE-2, 10BASE-T, 100BASE-TX, MIDI, ZV port, CardBus, and IrDA. It goes without saying that a cable or other members may be used for the connector, instead. It is preferable that an expansion unit such as the image pickup device 200 supports plug-and-play or hot plug capabilities so as to update the system immediately upon connecting to the notebook PC 100.

Referring now to FIGs. 2 through 16, a description will be given of a shape and structure of the CCD camera 200 as one exemplified embodiment of the present invention. FIGs. 2 through 5 are respectively a front view (FIG. 2), a right side view (FIG. 3), a left side view (FIG. 4), and a top view (FIG. 5) of the CCD camera 200 with its movable portion 220 raised (opened) from its anchor portion 210 for showing a state in which a USB connector 250 and a reinforcing portion 260 are stored in the anchor portion 210. FIGs. 6 through 10 are respectively a front view (FIG. 6), a right side view (FIG. 7), a left side view (FIG. 8), a top view (FIG. 9), and a rear view (FIG. 10) of the CCD camera 200 with its movable portion 220 raised from its anchor portion 210 for showing a state in which a USB connector 250 and a reinforcing portion 260 are projected from the anchor portion 210. FIGs. 11 and 12 are respectively a front view and a right side view of the CCD camera 200 with its movable portion 220 folded (closed) into its anchor portion 210. FIG. 13 is a sectional view of the CCD camera 200 showing a state in which a USB connector 250 and a reinforcing portion 260 are projected. FIG. 14 is a sectional view of the CCD camera showing a state in which a USB connector 250 and a reinforcing portion 260

are stored. FIG. 15 is a rear view of the notebook PC 100 to which the CCD camera 200 is attached. FIG. 16 is a right side view of the CCD camera 200 for explaining a stand 270 for the CCD camera 200.

As described above, the CCD camera 200 includes an anchor portion 210, a focus lens 230, a shutter 240, a USB connector 250, a reinforcing portion 260, and a stand 270.

The anchor portion 210 is attached through the USB connector 250 and the reinforcing portion 260 to the notebook PC 100 in such a manner as not to rotate. The anchor portion 210 includes a storage portion 212 of the focus lens 230 as shown in FIGS. 3, 4, 7 and 8. Accordingly, as best shown in FIG. 12, the focus lens 230 is stored in the storage portion 212 when the movable portion 220 is closed, and thus prevented from breaking when unused. In addition, the anchor portion 210 includes a pivot portion 214 constituting an axis of a pivoting movement of the movable portion 220 in a direction A, as will be discussed later.

The movable portion 220 includes first and second movable portions 222 and 224. The first movable portion 222 may pivot about a shaft (not shown) that pierces the first and second movable portions 222 and 224, in a direction B as shown in FIGS. 2 and 6, with respect to the second movable portion 224. The second movable portion 224 may pivot about a shaft (not shown) that pierces the pivot portion 214 and the second movable portion 224, in a direction A as shown in FIGS. 3, 4, 7 and 8, with respect to the anchor portion 210.

The USB connector 250 and the reinforcing portion 260 are stored in the anchor portion 210 so that it can project out to the left as shown in FIGS. 2 through 10. Each member may project synchronously or separately. An exemplary projection mechanism for each member is shown in FIGS. 10, 13, and 14. In these drawings, the USB connector 250 and the reinforcing portion 260 are connected via members 252

and 262 to each other, and synchronously move between a projection position and a storage position by shifting a button 264 shown in FIGs. 10, 13, and 14 in a direction C.

In contrast to the present embodiment, the USB connector 250 and the reinforcing portion 260 may be provided on a right, front, or rear side, or other portions, and connected to the notebook PC 100 in a position opposite to that in the present embodiment. In addition, the USB connector 250 and/or the reinforcing portion 260 to be provided may come more than one in number as necessary.

Since any structures known in the art may be applied to the focus lens 230, the shutter 240, and its other necessary imaging structures, a detailed explanation will now be omitted. An image captured through the lens 230 are transmitted by way of the USB connector 250 and a connector portion (not shown) in the notebook PC 100 to an information processing portion in the notebook PC 100. Also, this image is displayed on the LCD screen 12. Consequently, a user may edit the image using image-editing software as known in the art.

The reinforcing portion 260 serves to prevent the connector 250 from breaking by application of moment of a force by the CCD camera 200 based on its own weight. As shown in FIG. 6, the reinforcing portion 260 is placed under the connector 250. As specifically illustrated in FIG. 13, the reinforcing portion 260 includes a cutaway portion 266 which mates with a part of the external frame 22 of the base 22 in the notebook PC 100 shown in FIG. 15. In other words, the notebook PC 100 includes an aperture 24 through which the reinforcing portion 260 is inserted into the base 20. The external frame 22 near the aperture 24 can be wrought into a desired shape.

The stand 270 serves to adjust the height of the CCD camera 200, and as necessary, to partially tilt its orientation. Its height adjustment capability can

009594513-061600

accommodate variations of the height among the kinds of the notebook PC 100 to be connected. Its tilt adjustment capability can tilt the anchor portion 210 of the CCD camera 200 so as to be brought into alignment with the keyboard 40 of the notebook PC 100 to be connected that would be tilted toward a user (so as to raise its rear side having the LCD screen 12) for ergonomic purposes (*i.e.*, for convenience in typing). Such a tilt adjustment mechanism of the stand 270 may adjust the CCD camera 200 itself so as to be kept in a horizontal position even if a footprint P where the CCD camera is placed is tilted. For example, in FIG. 16, the footprint P where the CCD camera 200 is placed descends to the right, but the stand 270 serves to maintain lateral balance with its height adjustment mechanism and/or tilt adjustment mechanism, keeping the camera 200 in a horizontal position. From the foregoing it will be seen that the stand 270 may align the heights of the CCD camera 200 and the notebook PC 100 to which the CCD camera 200 is connected, even if the heights vary between them relative to a footprint P, and may keep the CCD camera in a horizontal position even if the footprint P is tilted, thereby reducing a stress arising in the connector 250.

FIG. 15 shows a state in which the USB connector 250 and the reinforcing portion 260 are connected to the notebook PC 100, and their heights are adjusted by the stand 270. It will be understood that the height adjustment capability that the stand 270 has makes the connector 250 and the reinforcing portion 260 connected to the notebook PC 100 in a horizontal position. This may reduce the stress arising in the connector 250, and avoid deteriorating the connector 250.

A description will be given of another exemplary configuration of the CCD camera 220 connected to the notebook PC 100, with reference to FIGs. 17 and 18. FIG. 17 is a right side view of the CCD camera 200 with its movable portion 220 tilted approximately 180 degrees relative to its anchor portion 210 for showing a state in which its attachment portion 280 is projected from the anchor portion 210. FIG. 18 is

00594513-061600

a right side view showing a state in which the CCD camera 200 shown in FIG. 17 is attached to an LCD bezel frame 10 of a notebook PC 100.

The attachment portion 280 is provided on the anchor portion 210 of the CCD camera 200. The attachment portion 280 includes a holding plate 282 that can be stored in an area 216 of the anchor portion 210, a column 284 that includes the holding plate 282 at its end and can be projected from the anchor portion 210. The attachment portion 280 may also include, as necessary, a mechanism for locking the attachment portion 280 in the state as shown in FIG. 17. Similarly, the movable portion 220 may also include a mechanism for locking the movable portion 220 into the anchor portion 210 in the state as shown in FIG. 17.

The attachment portion 280 may be engaged with the notebook PC 100 by projecting the column 284 from the anchor portion 210 and inserting a top portion of the LCD bezel frame 10 between the holding plate 282 and the anchor portion 210. At that time, the notebook PC 100 and the CCD camera 200 may be connected, for instance, via a USB cable 254. The USB cable 254 may be directly connected to the notebook PC 100. The CCD camera 100 as shown in FIGs. 2 through 16 may either include the USB cable 254, or not. The CCD camera 200 may be used at a height different from a conventional configuration by mounting the CCD camera 200 on the LCD bezel frame 10. In addition, the CCD camera 200 is allowed to ensure its shooting range as far as the cable 254 can extend.

Instead of the cable 254, the notebook PC 100 may use a wireless communication means such as an infrared data communication protocol to communicate with the anchor portion 210. Among infrared data communication protocols, IrDA known in the art may be utilized, as a great number of the notebook PCs may be equipped with an IrDA port. The IrDA port may be provided at any place on the body of the notebook PC 100. In that event, information captured

through the CCD camera 200 is transmitted directly to the notebook PC 100.

It is to be noted that the illustrated shape of the attachment portion 280 is exemplary only. Accordingly, if necessary, the attachment portion 280 may be configured to be replaceable with other structural member. Further, any shape attachable to at least other apparatus except for itself (image pickup device) may be enough for the attachment portion 280 of the present invention, and the apparatuses to which the image pickup device 200 can be attached are not restricted to the electronic apparatus 100 to which the image pickup device 200 is electrically or optically connected (e.g., portable information processor, and notebook PC), but may be other apparatuses. Such other apparatuses may not necessarily be electronic apparatuses such as a desk, a partition, and other office automation appliances. Moreover, a tripod, a bookshelf, a bookend, and the like may be included in the above other apparatuses, and the present invention covers the image pickup device 200 attachable to such apparatuses.

Although certain preferred embodiments of the present invention have been described above, various changes and modifications may be made in the present invention without departing from the spirit and scope thereof.

As described above, the image pickup device of the present invention due to its inclusion of a reinforcing portion would reduce a stress arising in the connector when it connects to the main body of the notebook PC, etc., and prevent the connector from deteriorating, while keeping the main body compact by allowing the reinforcing portion to be stored and projected. Furthermore, the image pickup device of the present invention is attachable to any external device including the liquid crystal display (LCD) of the notebook PC, and thus can change its height and position.

WHAT IS CLAIMED IS:

1. An image pickup device comprising:
a connector that is connectible with an electronic apparatus; and
5 a reinforcing portion that is located near said connector and reinforces
said connector when said electronic apparatus and said connector connect with each
other.

2. An image pickup device according to claim 1 further comprising an
10 anchor portion and a movable portion, said movable portion including an image pickup
portion, and said connector and said reinforcing portion being placed on said anchor
portion.

3. An image pickup device according to claim 2, wherein said
15 reinforcing portion is stored in said anchor portion so that said reinforcing portion can
project from said anchor portion.

4. An image pickup device according to claim 2 further comprising a
stand that is connected with said anchor portion and serves to adjust a height of said
20 anchor portion.

5. An image pickup device according to claim 4, wherein said stand also
serves to adjust a tilt of said anchor portion.

6. An image pickup device according to claim 2, wherein said anchor
25 portion includes a storage portion that can store said image pickup portion.

7. An image pickup device comprising:

a connector that is connectible with an electronic apparatus; and

an attachment portion that enables said image pickup device to be attached to an external apparatus.

5

8. An image pickup device according to claim 7, further comprising an

anchor portion and a movable portion, said movable portion including an image pickup portion, said connector being placed on said anchor portion, and said attachment portion enabling said anchor portion to be attached to the external apparatus.

10

9. An image pickup device according to claim 8, wherein said attachment portion can be provided onto said anchor portion so that attachment portion can project from said anchor portion.

15

10. An image pickup device according to claim 8, wherein said electronic apparatus includes a display portion, and said attachment portion is attachable to said display portion.

11. An image pickup device according to claim 1, wherein said connector

20 includes a USB interface.

12. An image pickup device according to claim 7, wherein said connector

includes a USB interface.

25

ABSTRACT OF THE DISCLOSURE

The present invention aims at providing a function-expansion unit for an electronic apparatus that may reduce the stress onto a connector, and provides a high
5 stability with a CCD camera. The CCD camera includes a reinforcing member under its connecting portion and a height-adjustable stand, thereby reducing the stress that would otherwise apply to the USB connector as the connecting portion, enhancing the connection, preventing connector's deterioration in the course of time, and allowing the CCD camera to be stably placed.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

Declaration and Power of Attorney for U.S. Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

IMAGE PICKUP DEVICE ATTACHABLE TO

ELECTRONIC APPARATUS

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約
国際出願番号を _____ とし、
(該当する場合) _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

11-246287

(Number)

(番号)

JAPAN

(Country)

(国名)

(Number)

(番号)

(Country)

(国名)

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

☐

31/08/1999

(Day/Month/Year Filed)

(出願年月日)

(Day/Month/Year Filed)

(出願年月日)

☐

私、第35編米国法典119条(e)項に基づいて下記の米國特許出願規定に記載された権利をここに主張いたします。

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米國特許出願に記載された権利、又は米國を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米國特許出願に開示されていない限り、その先行米國出願書提出日以降で本出願書の日国内または特許協力条約国際提出日まで期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、係属中、放棄済)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づく表明が全て真実であると信じていること、さらに故意にされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration (日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して送付する弁護士または代理人として、下記の者を指名いたします。(弁護士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)
See list of attorneys and/or agents on page 5.

書類送付先

Send Correspondence to:

ARMSTRONG, WESTERMAN, HATTORI,
McLELAND & NAUGHTON
1725 K Street, N.W., Suite 1000
Washington, D.C. 20006

直接電話連絡先: (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Telephone: (202) 659-2930 Fax: (202) 887-0357

唯一または第一発明者名	Full name of sole or first inventor	
発明者の署名	日付	Date
住所	Inventor's signature	Date
国籍	Residence	May 15, 2000
私書箱	Citizenship	
	Post Office Address	
	5200 Patric Henry Drive, Santa Clara, CA 95054, U.S.A.	
第二共同発明者	Full name of second joint inventor, if any	
第二共同発明者	日付	Date
住所	Second inventor's signature	Date
国籍	Residence	May 15, 2000
私書箱	Citizenship	
	Post Office Address	
	C/O FUJITSU GENERAL LIMITED 1116 Suenaga, Takatsu-ku, Kawasaki-shi, Kanagawa 213-8502, Japan	

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)

第三共同発明者		Full name of third joint inventor, if any	
第三発明者の署名	日付	Third inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	
第四共同発明者		Full name of fourth joint inventor, if any	
第四発明者の署名	日付	Fourth inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	
第五共同発明者		Full name of fifth joint inventor, if any	
第五発明者の署名	日付	Fifth inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	
第六共同発明者		Full name of sixth joint inventor, if any	
第六発明者の署名	日付	Sixth inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	

List of attorneys and/or agents

James E. Armstrong, III, Reg. No. 18,366; William F. Westerman, Reg. No. 29,988; Ken-Ichi Hattori, Reg. No. 32,861; Le-Nhung McLeland, Reg. No. 31,541; Ronald F. Naughton, Reg. No. 24,616; John R. Pegan, Reg. No. 18,069; William G. Kratz, Jr., Reg. No. 22,631; James P. Welch, Reg. No. 17,379; Albert Tockman, Reg. No. 19,722; Mel R. Quintos, Reg. No. 31,898; Donald W. Hanson, Reg. No. 27,133; Stephen G. Adrian, Reg. No. 32,878; William L. Brooks, Reg. No. 34,129; John F. Carney, Reg. No. 20,276; Edward F. Welsh, Reg. No. 22,455; Patrick D. Muir, Reg. No. 37,403; Gay A. Spahn, Reg. No. 34,978; John P. Kong, Reg. No. 40,054; and Luke A. Kilyk, Reg. No. 33,251.

009190 212546560